

生コンクリート価格スライド表

単位水量指定によるAE減水剤と高性能AE減水剤の区分表

《標準期》

○:AE減水剤、●:高性能AE減水剤

呼び強度スランプ 単位水量 セメントの種類	175Kg/m ³ 以下					180kg/m ³ 以下					185kg/m ³ 以下				
	N	H	BB	M	L	N	H	BB	M	L	N	H	BB	M	L
24-15	○	—	○	○	○	○	○	○	○	○	○	○	○	○	○
27-15	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○
30-15	○	●	○	○	○	○	○	○	○	○	○	○	○	○	○
33-15	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
36-15	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
24-18	—	—	—	—	—	—	—	—	—	—	○	—	○	○	○
27-18	●	●	●	●	●	●	●	●	●	●	○	●	○	○	○
30-18	●	●	●	●	●	●	●	●	●	●	○	●	○	○	○
33-18	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
36-18	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

《夏期》

呼び強度スランプ 単位水量 セメントの種類	175Kg/m ³ 以下					180kg/m ³ 以下					185kg/m ³ 以下				
	N	H	BB	M	L	N	H	BB	M	L	N	H	BB	M	L
24-15	○	—	○	○	○	○	○	○	○	○	○	○	○	○	○
27-15	○	●	○	●	○	○	○	○	○	○	○	○	○	○	○
30-15	●	●	○	●	○	○	○	○	○	○	○	○	○	○	○
33-15	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
36-15	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
24-18	—	—	—	—	—	—	—	—	—	—	○	—	○	○	○
27-18	●	●	●	●	●	●	●	●	●	●	○	●	○	○	○
30-18	●	●	●	●	●	●	●	●	●	●	○	●	○	○	○
33-18	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
36-18	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

注1) 上記区分表にない組合せについては、予め協同組合へお問い合わせください。

注2) 人工軽量コンクリートは別途協議とする。